

Magpol Kimya

magpol

## DATASHEET

# MAXOPOL DK 2000

POLYPROPYLENE GLYCOL DIOL FOR PU FOAM AND CASE

### CHEMICAL COMPOSITION

*At room temperature viscous liquid*

### APPLICATIONS

*Maxopol DK 2000 is a 2000 molecular weight propylene glycol initiated polyether diol.*

*Maxopol DK 2000 is widely used for CASE applications.*

### TYPICAL PROPERTIES

PROPERTY	UNIT	VALUE
Appearance	-	clear liquid
Hydroxyl Value	mg KOH/g	54.5-57.5
Average Molecular Weight	g/mol	2000
Viscosity at 25 C	mPa.s	260-340
Water content	%	Max 0.02
Acidity	mg KOH/g	Max 0.1
Color	APHA	Max 60

### STORAGE STABILITY

*15 C - 30 C in closed drum IBC or Container for 12 months*

### SAFETY And HANDLING

*Please refer to to our Material Safety Data sheets*

### PACKAGING

*Tight head Drum,IBC or Bulk Container*

## DISCLAIMER

*The information and data contained in this publication is the best of our knowledge, true and accurate but any recommendations or suggestions which may be made are without guarantee since the conditions of use are beyond our control.*

*The product properties may be changed without any notice.*

*No liability, warranty or guarantee of product performance is created by this document.*

*It is the Buyer's responsibility to determine whether products are appropriate for Buyer's use and to ensure that Buyer's workplace and disposal practices are in compliance with applicable laws and regulations.*

*Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.*

*MAGPOL KİMYA SANAYİ ve TİCARET A.Ş*

*Yenişehir Mahallesi Osmanlı Bulvarı, Arwen İş Merkezi*

*B Blok No:5 D 10 34912 - Pendik - İSTANBUL - TURKEY*

*Tel : + 90 216 592 3992 Fax : +90 216 592 1774*

[www.magpolkimya.com](http://www.magpolkimya.com)

[info@magpolkimya.com](mailto:info@magpolkimya.com)