

## DATASHEET

# MAXONATE MDI 50

Mixture of 2,4'- and 4,4'-diphenylmethane diisocyanate (MDI).

### CHEMICAL COMPOSITION

*At room temperature viscous liquid*

### APPLICATIONS

*Maxonate MDI 50 is used for manufacture of adhesives, coating and flexible foams.*

### TYPICAL PROPERTIES

PROPERTY	UNIT	VALUE
Molar Mass	g/mol	250
Purity	g/100g	99.5
4,4'-isomer	g/100g	48
NCO-content	g/100g	33.5
Viscosity at 25 C	mPa.s	12
Density at 25 C	g/cm <sup>3</sup>	1.19
Hydrolysable chlorine	mg/kg	100

### STORAGE STABILITY

*15 C - 30 C in closed drum IBC or Container for 12 months*

### SAFETY And HANDLING

*Please refer to to our Material Safety Data sheets*

### PACKAGING

*Tight head Drum,IBC or Bulk Container*

## DISCLAIMER

*The information and data contained in this publication is the best of our knowledge, true and accurate but any recommendations or suggestions which may be made are without guarantee since the conditions of use are beyond our control.*

*The product properties may be changed without any notice.*

*No liability, warranty or guarantee of product performance is created by this document.*

*It is the Buyer's responsibility to determine whether products are appropriate for Buyer's use and to ensure that Buyer's workplace and disposal practices are in compliance with applicable laws and regulations.*

*Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.*

**MAGPOL KİMYA SANAYİ ve TİCARET A.Ş**

Yenişehir Mahallesi Osmanlı Bulvarı, Arwen İş Merkezi

B Blok No:5 D 10 34912 - Pendik - İSTANBUL - TURKEY

Tel : + 90 216 592 3992 Fax : +90 216 592 1774

[www.magpolkimya.com](http://www.magpolkimya.com)

[info@magpolkimya.com](mailto:info@magpolkimya.com)